

09 AI in Games

Tvorba a dizajn počítačových hier

Návrh a vývoj počítačových hier

Motivation

- We require opponents/teammates in games
- Non-playing characters are usually required to perform some tasks that require AI
 - Following the player, combat, strategic thinking...
- We require something that responds to user actions and imitates the behavior of human players
- Ideally, an AI should fool the players into thinking it is an actual human
 - To keep the immersion level high
 - Turing test

A little history

- Pac-man (1979) was one of the first games with character AI
- Very simple AI that decides at crossroads whether to follow the player, run from him, or take a random road
 - Used different states – scatter, chase...
- Each ghost has its personality – this determined behavior
 - New target tiles are determined based on personality at every crossroad
- It was still effective
- Randomness added a necessary factor – **unpredictable behavior**
- A completely predictable AI is usually easy to beat
 - After a few tries, the player has a detailed model of AI behavior



The Kind of AI in games

- Hacks
 - Games use a lot of hacks, not only in AI
 - Ad hoc solutions to specific problems
- Heuristics
 - Predictions that work most of the time (without guarantees)
- Algorithms - the “true” AI
 - Techniques that simulate behavior and are usually derived from how real people or animals make decisions and perform actions
- Machine Learning
 - Observe thousands of examples of player behavior
 - Derives its own algorithm on what to do

Hacks - “Game AI is not AI”

- Is the Pac-man example AI?
 - It's just generating random numbers and performing one of three actions based on the result
 - It's not an AI technique
- In Sims, a lot of actions are just pre-defined animation sequences
 - There is no actual AI going on
- More complex AI \neq better AI

Heuristics

- Approximate solutions to existing problems
- This is usually how the human mind solves problems
 - I lost my keys \Rightarrow remember when I last had them and go step by step
 - A simple heuristic just says how good an enemy's aim is
 - The lower the number, the smaller the chance they will hit you
- Common heuristics:
 - **Most constrained**
 - If we have two groups fighting, and one character in one group has a unique weapon that pierces through some unique armor, it should attack a character wearing that armor
 - **Most difficult first** – if you can buy a strong unit, do it instead of getting a few weak ones
 - **Most promising first** – perform the action that will improve your chances the most
 - E.g. Chess AI

Algorithms

- Some AI actions still require something more
 - Movement of characters
 - Decision making
 - Tactics or strategy
 - Analysis of game state and future game state
- “Academic” AI

Academic AI vs. Game AI

- Academic AI
 - Make the AI as smart as possible
 - Solve the problem as efficiently and precisely as possible
 - E.g. we need a 99.99% guarantee that a traffic camera identifies the license plate correctly
- Game AI
 - Make the player have fun
 - Provide interesting challenges for the player
 - React to the player
 - Be predictable enough for the player
 - Be believable enough to keep the illusion of a real being in control

Game State Analysis

- Process input data to simplify the decision process
- This is usually called *sensing* - you create senses for the AI
 - Vision
 - Hearing
 - Touch
 - Smell?
 - ...

Gameplay AI is a 3-step process

1. **Sense** – what can I see/hear/feel
 - Some senses can cheat!
2. **Think** – consider what I do based on what I am sensing
 - Process data from senses and decide what to do
3. **Act** - Perform actions I have decided to do
 - Walk to a destination
 - Attack someone
 - Use an item
 - ...

AI Difficulty

- For some games, creating skilled AI is simple
 - Counter-strike: aim & shoot to kill instantly
- Difficult \neq Fun
 - “Dumb down the AI” – sometimes misses, isn’t perfectly efficient
 - Rubber-banding – adjusting to the player to always offer a reasonable challenge
 - Trying waiting for 30 seconds in a racing game
- For more complex games, creating challenging AI is a complex task
 - StarCraft 2 – there are hundreds of options of what to do at any moment
 - Most difficult AI bots cheat, since the AI cannot compete with more skilled players
 - **Sense & Act** is easy, **Think** is the difficult part
- Chess has a much smaller possibility space - ble to simulate 15-20 into the future



An example: Sims



- When does a sim become hungry?
- What to do next, and what if the sim really has to go to the bathroom?
- These are several competing systems that are assigned weights
- Changing these weights alters the behavior of the sim
- Final decisions as to which action to perform are strongly affected by the weights of different systems
- When a sim is about to pass out of hunger, getting food becomes top priority
 - AI navigation will help move them to the nearest food source
- The weight of the hunger system represents the desire to get food

AI types in games

- Hard-coded
 - Deterministic behavior – such as turning on lights in exact hours every day in a house when you are on vacation (to scare away thieves)
- Randomization
 - Throwing in randomized behavior
 - Not always exact times to turn the lights on/off
 - Add a random time offset every day, say in range $\pm 60\text{min}$ (we could use normal distribution)
- Weighted randoms
 - Every possible next step is given a weight
 - When deciding what to do, we generate a random number in range $[0, W]$, where W is the sum of all weights for all possibilities
 - Some of the possibilities will happen more often than others


Weighted randoms example

- We have a creature that can perform 3 actions
 - Attack, Cast spell, Run away
- We assign weights to these actions, say 60%, 30%, 10%
- Very similar to the Sims example, but those weights change over time

```
X = RandomFromRange(0, 99);  
if (X < 60)  
    Attack();  
else if (X < 90)  
    CastSpell();  
else RunAway();
```


Finite State Machines (FSM)

- Very simple construct
- We have several states an entity can be in (sleeping, wary, attacking, running away...)
- We define rules to transition from one state to another
- There does not have to be a transition from each state into every other state
 - The transition **running away** \Rightarrow **sleeping** does not make sense
 - **Running away** \Rightarrow **wary** \Rightarrow **sleeping** makes much more sense
- We also define when these transitions from one state to another should happen



Finite State Machines (2)

- Based on the current state of the entity, we perform a selected action
- If the guard is in the patrol state, they might walk through corridors along a pre-defined path
- If they are attacking, they might be moving continuously towards the player while shooting from a gun
- Once their health becomes low, they decide to run
- A proximity mine can use the same “proximity” check as the guard




Finite State Machines (3)

- The decision making is encapsulated in the transition rules
- The transition rules can incorporate a certain degree of randomization
 - Such as an enemy running away at less than 15-25% health
- This is called **reactive AI**, it always reacts to some game event
- The other type is **active AI**, which constantly seeks the best possible option
 - A sim in Sims
 - An AI opponent in Starcraft 2

Decision trees

- Decision trees are a simple way of representing decision making
- The inner nodes of a decision tree are decisions with only two possible answers: **Yes** or **No**
- Each leaf node is an action node
- Each node has two children
 - one for the Yes answer, one for the No answer
- We traverse the tree from the node
 - Evaluate each condition
 - Until we reach an action
 - Then perform the action



Decision trees (2)


- We apply an action every time a decision needs to be made
- Decision trees can be shared, as can be individual nodes
- Decision trees are sometimes built-in visual tools
 - The programmer has written code for decision nodes and action nodes
 - The designer connects these to build an actual tree
- With each decision we ignore a whole sub-tree
 - This is relatively efficient even for hundreds of nodes
- The decision can actually take several frames to decide
 - We always save the node in which we pause the decision making
 - And then resume in the next frame
 - A bit risky since the situation can change abruptly, making the decision invalid

Decision trees (3)

- You can also have non-binary decision trees
- Such as a ProcessHealthNode that has 4 children based on how much health the character has
 - High health \Rightarrow attack
 - Medium health \Rightarrow cast protective spell
 - Low health \Rightarrow cast healing spell
 - Very low health \Rightarrow run away


Behavior Trees

- Widely used in games
- It's a tree composed of nodes
- Each node can return a status to its parent
 - **Success** – the operation of this node finished successfully
 - **Failure** – the operation failed
 - **Running** – the operation is still running
- Nodes can have parameters
- Nodes can respond to context
 - Game state
- Lots of Unity plugins for BT
- Built-in support in Unreal



Behavior Trees (2)


- Leaf nodes represent actions
 - State: Running, Success or Failure
 - E.g. **Open a door, Run towards the player**
- Composite nodes
 - Encapsulate multiple children
 - Execute children in some order
 - Returns what is returned from children
 - E.g. **Sequence, Selector**
- Decorator nodes
 - Have a single child node
 - Transform result from the child, repeat, terminate
 - E.g. **Inverter, Repeater**



Behavior Trees – Actions

- Action **Walk**
 - Parameters
 - Character
 - Destination – location or another character
 - **Running** On the way
 - **Success** Reached destination
 - **Failure** Failed to reach destination (blocked/died/stunned...)
- Init – called the first time the node is visited
- Process/Update – called every tick while the node is “running”

Halo 2




Fuzzy logic

- Decision trees work quite well, however it's still not realistic enough
 - Using absolute threshold values to decide
- There should be a range of values that allow for both decisions to happen
 - Proximity test
 - 5 meters is still too far sometimes
 - 7 meters is close enough sometimes
- The basic idea of **fuzzy logic** is that objects belong to multiple fuzzy sets by different amounts
 - A player partially behind cover can be in sets "in cover" as well as "exposed", however we assign percentages for each set \Rightarrow 60% in cover, 40% exposed

Fuzzy logic (2)

- The process of assigning the degrees of membership is called *fuzzification*
- In order to decide, we might have to *defuzzify* the membership degrees and give an exact result to which set we fully belong
- Simple fuzzification:
 - Cutoff values for fully belonging to a set
 - Proximity \Rightarrow 2 sets “near” and “far”
 - 4 meters = near, 7 meters = far
 - between 4 and 7 meters
 - weighted randomness decides



Fuzzy logic (3)

- Defuzzification is much harder
- From several degrees, we must choose the correct one
- Just generating a random number and considering which set is more likely to occur can work in some situations
- We cannot just take the set with the highest degree
 - fuzziness provides a chance for something unlikely to happen
- If the result is just a number, it is much easier to defuzzify
 - An AI might be cautious, when combined with the fact that the player is behind cover, we generate a number that says how long the AI will take to aim
- For boolean values, we determine a cutoff and then compare it to the degree

Fuzzy logic (4)

- The real power comes from rapid AI prototyping
 - If (distance < 20 AND health > 1) then Attack()
 - If (player is close AND I am healthy) then Attack()
- We are using two fuzzy sets in the example
- We need to redefine the AND, OR and NOT operators for fuzzy sets
 - It's no longer Boolean logic

$$\text{AND} \rightarrow P = \min(A, B)$$

$$\text{OR} \rightarrow P = \max(A, B)$$

A, B – degrees of membership

P – final probability

Utility theory

- *“Utility theory says that every state has a degree of usefulness, or utility, to an agent and that the agent will prefer states with higher utility.”*
- We take the current world state, think of what would happen if we performed some action
- What changes in the world state can be used to derive how much that agent improved its “happiness”
- Actions with the highest utility value are chosen and performed

Utility theory – examples

- Chess is perfect for executing Utility theory
 - If one action causes me to lose an important piece in the next move \Rightarrow most likely low utility value
 - There are exceptions of course
 - Predict all possible outcomes in the next few steps
 - Choose the step maximizing the utility value
- A strategy game considers multiple things
 - Troop strength
 - Base/worker safety
 - Estimated enemy strength
 - Research level, amount of resources




Utility theory in practice

- We make a copy of the game state, perform the action, evaluate what happened
- Some actions take time to complete, the utility value is then utility-over-time instead (e.g. DPS)
- We usually can make localized decisions, meaning we do not always need the whole game state
 - In Sims, a sim usually cares only about himself
 - If the sim is hungry, eating will improve his happiness the most
 - So he goes to the kitchen
- Might require player prediction
- In FPS games, the agents have simple utility preferences
 - Agents will be preferring states where they continue to live
 - And prefer when the player will have low health as a result of their actions


Goal-oriented action planning (GOAP)

- Utility theory decides what an agent wants to do, not HOW to do it
- GOAP is working with *goals*, which are desirable world states that the agent wants to achieve through performing actions
- A goal could be to kill the player
 - Attacking the player is one action that could result in just that
- An agent has multiple goals, but usually only one active at a time
- Two-stage process:
 - Select the most relevant goal
 - Solve a goal by executing a sequence of actions
- Goal selection can be solved using previous methods
 - Decision trees, utility theory, ...
- The second stage needs a special solution

<https://www.gamedeveloper.com/programming/postmortem-AI-action-planning-on-Assassins-Creed-Odyssey-and-Immortals-Fenyx-Rising->



GOAP (2)



- Say a character is hungry
 - You have no food, so you need to create a plan to obtain food
 - Could be going into the woods to hunt animals, then extract the meat, cook it, and finally eat it
- Each action has a set of conditions it can satisfy, as well as a set of prerequisites that need to be satisfied
 - Eating food requires cooking food
 - Cooking food requires having raw food
 - Having raw food requires buying raw food
 - Buying food requires money
 - Money requires a job
- The algorithm walks back through these preconditions and identifies which actions need to be executed

GOAP (3)

- A sequence of goals might not exist
- There are lots of problems with world representation
 - Not only for GOAP
 - I desire a world state in which I am not hungry
 - I desire a world state in which the player is dead
 - We need to generate this world state with preconditions and effects
- Searching through possible actions is also a problem
- Search for a shortest (or least difficult) path in a graph of actions
 - There are many ways to solve a goal
- We always walk back from the desired state to the current state, trying to find a way that could work
- Quite advanced, but allows for very “intelligent” AI

Path-finding

- Not really an AI technique, more of a support technique for other AI
- Simply searching for the shortest path from A to B in a level
- We have nodes and edges
- Nodes describe points that the agent must be able to reach
- Nodes are connected by edges, which are just straight lines
- An agent moves along an edge to get to another node
- To get to a neighboring node, you just rotate the agent and move them along the corresponding edge




Image from <https://en.wikipedia.org/wiki/Pathfinding>

Path-finding (2)

- Moving along straight lines is highly unnatural
 - Except for robots maybe
- Nodes may be in a grid, resulting in not very smooth motion
- A few possibilities to avoid this:
 - Irregularly placed nodes
 - Allow each node to have a tolerance as to how close the agent must be to consider that they visited the node
 - Placing an interpolation curve (e.g. piecewise bezier curve) through the nodes

Path-finding (3)

- Edges may be unidirectional, bidirectional, even weighted
- Higher weight means a harder to pass route
- Weights could even be different for different types of agents
 - Flying units versus ground units, or units that can walk up cliffs
 - Results in different paths taken by different agents
- Weights can be dynamic
 - Building something on top of existing nodes sets the weight to infinity
 - Flying units might try to avoid guard towers, so the guard towers increase the weight of nearby edges


A* path-finding (aka. A-star)

- There are lots of algorithms that solve the path-finding problem
- A* is the most used one
- Relatively fast to compute
- Has lots of modifications

https://en.wikipedia.org/wiki/A*_search_algorithm

Path-finding – taking it a step further

- Another common technique is called a **navigation mesh (navmesh)**
- It is a simple mesh that describes **all** walkable terrain in the level
 - Can be artist generated
 - Much better is when it's generated automatically
 - Might require some tweaking by artists or designers
- Triangles are nodes, edges are between neighboring triangles
- A* can be used, we just have to set the tolerance values based on the triangles



AI in Unity

- Very little AI support without plugins
 - Can use Unity's Animator for Finite State Machines
 - Can use Visual Scripting for Finite State Machines
- Has ML Agents package for reinforced learning
- Making your own is not that hard for simple games
- Lots of paid and a few free plugins
 - Behavior Designer, NodeCanvas, Apex Utility AI, Panda BT
- Simply coding it (no visual representation) is also OK
 - But think about configurability & the potential to modify it

AI in Unity

- Unity has built-in support for NavMesh Path-finding
 - Static NavMeshes
 - Dynamic obstacles and priorities
 - Rebuild NavMesh dynamically
 - Only for 3D
- For 2D
 - Use NavMeshPlus – <https://github.com/h8man/NavMeshPlus>
 - Built on top of Unity's 3D NavMesh
 - Use A* Pathfinding Project - has a free/paid version – <https://arongranberg.com/astar/>

References

- McShaffry, M., and Graham, D. *Game Coding Complete, Fourth Edition*. Course Technology PTR, 2012.
- Millington, Ian, and John D. Funge. *Artificial intelligence for games*. Burlington, MA: Morgan Kaufmann/Elsevier, 2009. Print.
- <https://www.gamedeveloper.com/programming/behavior-trees-for-ai-how-they-work>
- <https://www.gamedeveloper.com/programming/postmortem-AI-action-planning-on-Assassins-Creed-Odyssey-and-Immortals-Fenyx-Rising->